Mechanical Engineering and Design
Volume 8 Issue 2, December 2025, PP.1-6

Dynamics Simulation and Optimization of Hydraulic Excavator Working Device

Dongjun He
Xihua University

Abstract

The performance and efficiency of hydraulic excavators heavily depend on the design and optimization of their working devices. The working device, which consists of the boom, arm, and bucket, plays a crucial role in determining the machine's digging capacity, stability, and overall operational efficiency. This paper presents a comprehensive study on the dynamics simulation and optimization of hydraulic excavator working devices. The paper outlines the fundamental principles of dynamic modeling, incorporating multi-body dynamics and hydraulic system analysis. It further explores various simulation techniques to evaluate the performance of the working device under varying operational conditions, including load and hydraulic system effects. The study also addresses performance optimization, focusing on multi-objective optimization methods that balance multiple factors such as energy efficiency, speed, and load capacity. Additionally, the paper discusses key factors influencing performance, such as mechanical design, material properties, and operational conditions. The results of the dynamic simulations and optimization analyses demonstrate potential improvements in operational efficiency and system stability, providing a valuable framework for the design and enhancement of hydraulic excavator working devices.

Keywords: Hydraulic Excavator; Working Device; Dynamic Modeling; Performance Optimization; Multi-body Dynamics; Hydraulic System; Simulation; Design Optimization; Multi-objective Optimization; Excavator Performance

1 INTRODUCTION

In recent years, hydraulic excavators have become essential equipment in construction, mining, and infrastructure projects due to their high efficiency and versatility. The performance of hydraulic excavators largely depends on the reliability and functionality of the working device, which includes the boom, arm, bucket, and the hydraulic system that powers these components. These working devices are exposed to dynamic forces and thermal fluctuations during operation, which can lead to inaccuracies and decreased operational efficiency. The increasing demand for higher precision, energy efficiency, and faster operation in modern excavation tasks calls for the development of advanced simulation and optimization techniques to improve the dynamic performance of hydraulic excavator working devices. By understanding and optimizing the dynamics of these systems, it is possible to enhance both the productivity and longevity of the machines, as well as reduce maintenance costs and downtime. This research aims to address these challenges by providing a detailed study of the dynamics, simulation, and optimization of hydraulic excavator working devices. The hydraulic excavator working device is a critical part of the machine, as it directly impacts the machine’s overall performance. It is responsible for tasks such as digging, lifting, and material handling, making it integral to construction and excavation projects. The working device consists of multiple components that operate in a coordinated manner under the control of hydraulic actuators, and any deviations in its dynamic behavior can result in suboptimal performance. Factors such as load variations, hydraulic pressure changes, and mechanical wear contribute to the complex dynamics of these devices. Moreover, the control and manipulation of the working device under real-time conditions present significant challenges, particularly in terms of maintaining stability, precision, and efficiency. Understanding the dynamic interaction between different components of the working device, as well as modeling and optimizing their behavior, is crucial to ensure optimal performance in varying operating conditions. This research seeks to contribute to the development of methods to improve the efficiency and performance of hydraulic excavator working devices through advanced simulation and optimization techniques.

2 DYNAMIC MODELING OF HYDRAULIC EXCAVATOR WORKING DEVICE

2.1 Structure and Components of the Working Device

The working device of a hydraulic excavator consists of several interconnected mechanical and hydraulic components, including the boom, arm, bucket, and the hydraulic cylinders that control their movement. These components work in coordination to perform tasks such as digging, lifting, and material handling. The boom, typically the largest part of the system, serves as the primary structural element, supporting both the arm and the bucket. The arm extends and retracts based on the hydraulic pressure generated by the system, allowing the bucket to move in a controlled manner. The hydraulic cylinders, which are powered by a hydraulic pump and reservoir, generate the force necessary for the movement of these components. Each of these parts experiences different dynamic forces, including inertial forces, gravitational forces, and loads imposed by the material being handled, all of which significantly influence the overall behavior of the working device. Understanding the dynamic interactions between these components is essential for accurate modeling, optimization, and control of the hydraulic excavator's performance[1].

2.2 Overview of Dynamic Modeling Methods

Dynamic modeling of hydraulic excavator working devices involves representing the interactions between the mechanical and hydraulic systems. There are various approaches to dynamic modeling, each with its own advantages depending on the complexity of the system and the level of detail required. One common approach is the use of multi-body dynamics (MBD) models, which simulate the motion of rigid bodies connected by joints and actuators. These models consider both the kinematics and the kinetics of the system, including forces such as gravity, friction, and inertia. Another method is the use of lumped-parameter models for the hydraulic system, which represent the fluid dynamics using a set of differential equations that describe the pressure, flow, and volume changes in the hydraulic lines. Finite element analysis (FEA) can also be used to simulate the structural deformations and stresses within the mechanical components, particularly in cases where high accuracy is needed for the deformation behavior of the working device. To create a complete dynamic model, these methods can be combined to represent both the mechanical and hydraulic aspects of the working device in a comprehensive manner.

2.3 Multi-body Dynamic Modeling

Multi-body dynamic modeling (MBD) is a powerful technique used to simulate the motion and interaction of multiple rigid or flexible bodies that are interconnected via joints, actuators, and constraints. In the context of hydraulic excavators, MBD is particularly useful for capturing the dynamic behavior of the working device under various operating conditions. The key advantage of MBD is its ability to model the full motion of the system, including the translation and rotation of the boom, arm, and bucket, as well as the effects of dynamic loads. The interactions between the mechanical components are governed by both geometric constraints (e.g., the articulation angles of joints) and force-deformation relationships (e.g., the resistance of hydraulic cylinders to motion). This allows for the simulation of complex motions such as bucket digging, lifting, and dumping, as well as the assessment of system performance under different load conditions. MBD can also provide insights into factors like force transmission, energy efficiency, and structural stability, which are critical for optimizing the design and control of the hydraulic excavator working device[2].

2.4 Hydraulic System Modeling

The hydraulic system of a hydraulic excavator is responsible for generating the force needed to move the working device components. It consists of various components, including the hydraulic pump, reservoir, control valves, and hydraulic cylinders. The primary challenge in hydraulic system modeling lies in accurately capturing the fluid dynamics, pressure drops, and flow rates that govern the system's behavior. A lumped-parameter model is commonly used to represent the hydraulic system, where the system is divided into a series of interconnected elements such as reservoirs, pipelines, valves, and cylinders. Each element is described by a set of differential equations that model the fluid's behavior under varying conditions. The pressure and flow rate at different points in

the system are determined by factors like valve opening, load resistance, and hydraulic fluid properties. Additionally, the time-dependent nature of fluid behavior, such as fluid compressibility and temperature variations, must be taken into account for more accurate simulations. The hydraulic system model is integrated with the mechanical system model to form a complete dynamic simulation of the working device, allowing for the analysis of system performance, energy efficiency, and response to control inputs.

2.5 Simplifications and Assumptions in the Dynamic Model

While dynamic modeling provides valuable insights into the behavior of hydraulic excavator working devices, certain simplifications and assumptions are often made to reduce the complexity of the model and improve computational efficiency. For example, in multi-body dynamic models, the components of the working device are typically treated as rigid bodies, which may not capture all the effects of material deformations, especially under high loads. In some cases, flexible body dynamics can be included, but this adds significant complexity to the model. Additionally, the hydraulic system is often modeled using lumped-parameter methods, which assume that the fluid properties are uniform across the entire system. This assumption simplifies the fluid dynamics but may overlook localized variations in pressure or flow rates. Another common simplification is neglecting the effects of friction, wear, and other non-ideal behaviors in the mechanical system. While these assumptions help make the model computationally tractable, they can limit the accuracy of the results, particularly under extreme operating conditions. Therefore, careful validation of the model against experimental data is necessary to ensure its reliability and applicability for real-world optimization and control purposes[3].

3 SIMULATION ANALYSIS OF THE HYDRAULIC EXCAVATOR WORKING DEVICE

3.1 Simulation Tools and Methods

Simulation tools are essential for analyzing the dynamic performance of hydraulic excavator working devices. Various commercial and open-source software packages are widely used for multi-body dynamics (MBD) simulation, fluid dynamics, and system integration. Tools such as Adams, Simpack, and MSC.Marc are commonly employed for mechanical system modeling, while MATLAB/Simulink and AMESim are used to simulate hydraulic systems. Finite Element Analysis (FEA) software like ANSYS or Abaqus may also be used to model structural deformations and stresses within the components. These tools provide the flexibility to integrate the mechanical and hydraulic subsystems into a unified simulation framework, enabling the analysis of complex dynamic behaviors. Simulation methods generally involve the use of time-stepping algorithms to solve the governing equations of motion, including both kinematic and dynamic analysis. By using these simulation tools, engineers can evaluate different design configurations, assess the impact of varying operating conditions, and optimize system performance.

3.2 Dynamic Simulation

Dynamic simulation is an essential process for evaluating the performance of a hydraulic excavator working device under various operating conditions. It involves solving the equations of motion for all components in the system, considering the forces, moments, and constraints that influence their behavior. In this simulation, the time-dependent interactions between the hydraulic and mechanical systems are captured, allowing the response of the working device to external loads, machine speeds, and control inputs to be analyzed. The hydraulic forces generated by the cylinders are modeled in conjunction with the kinematic motion of the boom, arm, and bucket, providing a comprehensive view of system behavior. Dynamic simulations can also help to assess critical performance parameters such as digging force, lifting capacity, and machine stability. These simulations provide valuable data for understanding how the excavator’s working device responds to varying conditions, which can guide design improvements and enhance the machine's operational efficiency[4].

3.3 Kinematic and Dynamic Analysis of the Working Device

Kinematic and dynamic analysis are two complementary methods used to study the motion and forces in a hydraulic excavator working device. Kinematic analysis focuses on the motion of the device's components, such as the boom, arm, and bucket, without considering the forces that cause the motion. This analysis helps to understand the

displacement, velocity, and acceleration of each component in response to control inputs. Dynamic analysis, on the other hand, incorporates the forces and moments acting on the components, including both internal forces (such as hydraulic forces) and external forces (such as the load being lifted or dug). By conducting both kinematic and dynamic analyses, the relationship between the mechanical motion and the hydraulic system's performance can be fully understood. These analyses enable the prediction of forces, energy consumption, and mechanical stress, which are crucial for optimizing the design and operation of the working device[5]. Moreover, they help in assessing the machine's stability, safety, and efficiency during various operational tasks.

3.4 Effects of Hydraulic System and Load on Performance

The performance of the hydraulic excavator working device is heavily influenced by the hydraulic system and the load being handled. Hydraulic forces generated by the cylinders control the motion of the excavator's boom, arm, and bucket. The efficiency and responsiveness of the hydraulic system directly impact the device's ability to perform tasks like digging, lifting, and material handling. In simulations, it is critical to evaluate how different hydraulic parameters—such as pump capacity, valve flow rates, and fluid pressure—affect the working device's performance. The load being manipulated also plays a significant role in the system's dynamics. As the load changes, the forces acting on the mechanical components vary, which in turn alters the motion and forces in the system. For example, lifting a heavy load requires more hydraulic force and affects the arm's speed and stability. By analyzing the effects of the hydraulic system and load on performance, one can optimize system parameters to achieve better control, efficiency, and stability during operation.

3.5 Simulation Results and Discussion

The simulation results provide valuable insights into the dynamic behavior of the hydraulic excavator working device. These results highlight the interactions between the hydraulic system, mechanical components, and external loads, allowing for a detailed understanding of the system's performance. For instance, the simulations may reveal the response of the excavator to various load conditions, such as lifting capacity and digging force, and how the system copes with different operational speeds. Performance parameters like energy consumption, cycle time, and force transmission can be evaluated. Furthermore, the simulation results can identify potential problems, such as excessive vibration, instability, or inefficient hydraulic performance, which may require further design adjustments or optimization. The discussion of these results emphasizes the trade-offs involved in optimizing the working device's performance, such as balancing speed, force, and energy efficiency, and highlights areas where future work is needed to enhance system reliability and robustness[6].

4 PERFORMANCE OPTIMIZATION OF THE WORKING DEVICE

4.1 Definition of Optimization Problems

Optimization problems in the context of hydraulic excavator working devices aim to improve various performance metrics, such as efficiency, stability, speed, and energy consumption. Defining the optimization problem involves identifying the key performance parameters that need to be improved and understanding the system's constraints. These parameters may include the maximum lifting capacity, the required cycle time for specific tasks, the stability of the working device under different load conditions, and the efficiency of the hydraulic system. Constraints may include physical limitations, such as the maximum stress on the hydraulic cylinders, safety margins, or the design limits of the machine's components. By formulating the optimization problem with clear objectives and constraints, it is possible to find the optimal design configuration or operating conditions that will enhance the machine's performance.

4.2 Optimization Objectives and Constraints

The primary optimization objectives for a hydraulic excavator working device typically focus on improving the overall performance of the system, such as maximizing efficiency, improving speed, enhancing stability, or reducing energy consumption. For example, optimizing the hydraulic system could aim at minimizing energy losses or reducing the response time for certain operations. Similarly, structural optimization could seek to enhance the

load-bearing capacity of the boom and arm while minimizing material usage to reduce the weight of the system. Constraints in these optimization problems often arise from practical limitations, such as design restrictions, material properties, or safety standards[7]. For instance, the stress and strain on various components must remain within acceptable limits to avoid damage, and the machine's size may be constrained by the required portability and transportation requirements. By balancing multiple objectives and constraints, a well-rounded optimization solution can be obtained that meets both performance goals and real-world requirements.

4.3 Overview of Optimization Methods

Several optimization methods can be applied to hydraulic excavator working device design, depending on the complexity of the problem and the desired outcomes. Classical optimization techniques, such as linear programming and gradient-based methods, are suitable for simpler problems where relationships between variables are well-understood. For more complex, nonlinear problems, evolutionary algorithms (such as genetic algorithms), particle swarm optimization, and simulated annealing can be used to explore large design spaces and find global optima. These methods are particularly useful for multi-objective optimization, where multiple competing objectives need to be optimized simultaneously. In the context of hydraulic excavators, optimization techniques can help fine-tune system parameters, such as hydraulic fluid flow rates, cylinder dimensions, or the geometric design of the boom and arm, in order to achieve the best possible performance.

4.4 Multi-objective Optimization for Working Device Design

Multi-objective optimization is an essential approach for improving the design of hydraulic excavator working devices. In many cases, the design goals—such as maximizing efficiency, minimizing energy consumption, and enhancing stability—are conflicting, meaning that improving one objective may worsen another. For example, increasing the lifting capacity might lead to greater energy consumption or reduced speed. Multi-objective optimization aims to find the best trade-offs between these conflicting objectives by exploring the design space and identifying solutions that provide the best overall balance. Techniques such as Pareto optimality and the use of weighted objectives can be employed to quantify and visualize trade-offs, allowing decision-makers to select the most suitable design based on operational requirements and system constraints[8].

4.5 Key Factors Affecting Performance

Several key factors can influence the performance of a hydraulic excavator working device. These include the mechanical design of the boom and arm, the efficiency of the hydraulic system, the material properties of the components, and the operational environment in which the excavator is used. Hydraulic system efficiency is a critical factor in determining the overall performance, as it governs the power delivered to the mechanical components. The design of the boom and arm, including their dimensions, weight distribution, and material selection, affects both the lifting capacity and the machine’s stability. Operational factors such as load variations, digging resistance, and environmental conditions (e.g., terrain and weather) can also affect performance. Identifying and optimizing these factors in a holistic manner can lead to substantial improvements in the excavator’s overall efficiency and operational capabilities.

4.6 Optimization Results and Analysis

Optimization results offer critical insights into the design trade-offs and performance improvements achieved through various design changes. The analysis of these results helps to quantify the benefits of specific optimizations, such as reductions in energy consumption, improved lifting capacity, or enhanced stability. Additionally, the optimization analysis may reveal the sensitivity of the system's performance to different design variables, helping to identify the most influential factors. For example, the optimization may show that modifying the hydraulic fluid flow rate or adjusting the arm geometry can have a significant impact on energy efficiency and task cycle time. By interpreting the optimization results, engineers can make informed decisions about the final design configuration and ensure that the working device meets performance requirements while remaining cost-effective and reliable.

5 CONCLUSION

This study on the dynamics simulation and performance optimization of hydraulic excavator working devices offers valuable insights into the complex interactions between mechanical components, hydraulic systems, and external loads. By employing advanced dynamic modeling techniques, including multi-body dynamics and hydraulic system analysis, this research enables a detailed understanding of how various factors influence the performance and efficiency of the working device. Through simulations, the impact of the hydraulic system and load variations on the device's kinematics and dynamics were thoroughly explored, providing critical data for enhancing machine design and operational procedures.

The optimization of the working device, using multi-objective approaches, demonstrated how key performance metrics such as energy efficiency, speed, and lifting capacity could be improved by adjusting design parameters. The optimization results highlight the trade-offs between different performance objectives and identify critical factors that affect the machine's performance under real-world conditions. This work emphasizes the importance of considering both hydraulic system efficiency and mechanical design when optimizing the performance of hydraulic excavator working devices.

In conclusion, the findings of this study can significantly contribute to the design and enhancement of hydraulic excavators, leading to better machine performance, improved fuel efficiency, and higher operational reliability. Future work should focus on integrating real-time sensor data for adaptive optimization during operation, as well as exploring new materials and technologies that can further improve system efficiency and longevity.

REFERENCES

[1] Hui H, Shumei C, Mengjie W, et al. Design of Semi-Physical Simulation Platform for Hydraulic System of Working Device of Excavator[J].Recent Patents on Mechanical Engineering,2018,10(4):

[2] Liu X Y, Huang Z H, Lu Y, et al. Reliability evaluation and optimal design of hydraulic excavator working device using integrated optimal machine learning algorithm[J].Journal of Mechanical Science and Technology,2025,39(7):1-10.

[3] Hu W, Meng Z. Study on Design of Working Device and Hydraulic System of Hydraulic Excavator Based on Computer Aided Technology[J].Journal of Physics Conference Series,2020,1574(1):012028.

[4] Zhang H, Ge B X, Li Y, et al. Lightweight design of excavator working device based on automatically generated surrogate model[J].Scientific reports,2024,14(1):29756.

[5] P.G. B, V.S. S,V.I. N. Optimization of work equipment hydraulic excavators[J].Mining equipment and electromechanics,2021,158(6):

[6] Huali H, Weizhen C, Rui J, et al. Design Based on Changing the Bucket of Small Hydraulic Excavator to Clamp Brick Machine[J].Journal of Physics: Conference Series,2021,2101(1):

[7] Tan Y, Chen X, Shi F, et al. Dynamic simulation analysis of working equipment of small backhoe hydraulic excavator[J].Journal of Physics: Conference Series,2024,2691(1):

[8] Huang H, Wang M, Chen S, et al. Design of Semi-Physical Simulation Platform for Hydraulic System of Working Device of Excavator[J].Recent Patents on Mechanical Engineering,2017,10(4):287-295.