

Research on Tool Wear Prediction of CNC Machine Tools Based on Digital Twin

Dongjun He

Xihua University

Abstract

The prediction of tool wear in CNC machine tools is a critical aspect of ensuring the efficient operation and longevity of manufacturing equipment. Tool wear significantly impacts machining accuracy, surface finish quality, and operational downtime, making its prediction essential for proactive maintenance strategies. This paper explores the integration of Digital Twin technology with tool wear prediction models to enhance the precision and reliability of wear forecasting in CNC machines. We review existing methodologies for tool wear prediction, including physics-based models, data-driven approaches, and hybrid models, with an emphasis on their strengths and limitations. Furthermore, the paper highlights the role of Digital Twin technology in creating real-time, virtual replicas of CNC machines that can dynamically monitor tool wear and provide actionable insights for optimization. By leveraging real-time data and advanced simulation techniques, Digital Twin-based prediction models offer significant improvements over traditional methods. The paper concludes by discussing future directions for integrating machine learning, deep learning, and real-time data analytics into the tool wear prediction process, ultimately contributing to the development of more intelligent and adaptive manufacturing systems.

Keywords: *Tool Wear Prediction; CNC Machines; Digital Twin; Predictive Maintenance; Machine Learning; Hybrid Models; Real-Time Monitoring; Optimization*

1 INTRODUCTION

CNC (Computer Numerical Control) machine tools have become indispensable in modern manufacturing due to their precision, flexibility, and ability to handle complex machining tasks. These machines are used across a wide range of industries, including aerospace, automotive, and electronics, to produce high-quality parts with intricate geometries. However, the performance of CNC machines is significantly impacted by tool wear, which occurs over time due to the constant mechanical, thermal, and chemical stresses experienced by the cutting tools during operation. Tool wear not only affects the accuracy of the machining process but also results in increased production costs, reduced efficiency, and even tool failure if left unmonitored. Consequently, understanding and predicting tool wear in real-time is crucial for maintaining optimal performance in CNC machine tools. Traditional approaches to tool wear detection often rely on manual inspections or indirect measurements, which are both time-consuming and prone to human error. Therefore, there is a strong need for advanced technologies that can predict tool wear accurately, enabling timely interventions to prevent unexpected tool failures and reduce downtime. One promising solution to this problem lies in the application of Digital Twin (DT) technology. A Digital Twin is a virtual replica of a physical system, such as a CNC machine, that uses real-time data from sensors and other monitoring tools to simulate and predict the behavior of the system. By leveraging this technology, it is possible to create a dynamic model that continuously tracks and predicts tool wear in CNC machine tools, providing valuable insights into their operational performance and helping to optimize maintenance schedules.

2 THEORETICAL FOUNDATION OF TOOL WEAR PREDICTION

2.1 CNC Tool Wear Models

CNC tool wear is a progressive process that affects the cutting efficiency and accuracy of the machining process.

Various models have been proposed to describe and predict tool wear in CNC machines. These models generally fall into two categories: empirical models and mechanistic models. Empirical models rely on experimental data and statistical methods to establish relationships between operational parameters (such as cutting speed, feed rate, and depth of cut) and tool wear. While empirical models are simple to implement, their accuracy is limited to specific conditions and materials, making them less adaptable to different machining scenarios.

Mechanistic models, on the other hand, attempt to describe the underlying physical processes responsible for tool wear. These models often consider factors such as cutting forces, temperature distribution, and material properties. A widely used mechanistic approach is the cutting force-based model, which correlates the wear rate with the cutting forces exerted on the tool during the machining process. Thermal models, which consider the heat generated in the cutting zone, are also commonly applied as heat is a major contributor to tool degradation. Additionally, some hybrid models combine both empirical and mechanistic approaches to improve predictive accuracy across a broader range of conditions^[1].

In recent years, machine learning and data-driven approaches have been integrated with traditional tool wear models, allowing for real-time predictions based on sensor data. These advanced models have shown promise in improving the accuracy and generalizability of tool wear predictions, making them valuable tools for modern manufacturing environments.

2.2 Factors Influencing Tool Wear

Tool wear is a multifaceted phenomenon influenced by a wide range of factors, each of which can affect the rate and type of wear experienced by the tool. The most prominent factors include cutting parameters, material properties, tool material, and environmental conditions.

Cutting parameters such as cutting speed, feed rate, and depth of cut play a significant role in determining the wear rate. Higher cutting speeds and feed rates typically lead to increased thermal and mechanical stress on the tool, accelerating wear. The hardness and toughness of the workpiece material also influence wear behavior, as harder materials cause more abrasive wear, while tougher materials may lead to adhesive wear.

The tool material itself plays a crucial role in determining its wear resistance. High-performance materials such as carbide, ceramic, and cermet are often used for machining harder materials due to their higher hardness and thermal stability. However, even the best tool materials experience wear under extreme conditions, which is why understanding the wear mechanisms is critical for designing effective tool wear prediction models.

Environmental factors, such as lubrication, coolant type, and temperature, can also impact the wear process. For instance, insufficient lubrication can increase friction and accelerate tool degradation. Conversely, proper coolant application can lower the cutting temperature, thereby reducing thermal wear. External factors, such as vibrations and machine dynamics, can further exacerbate tool wear by introducing additional stresses during machining^[2].

2.3 Fundamentals of Digital Twin Technology

Digital Twin technology represents the virtual representation of a physical asset or system, providing real-time data and insights through continuous monitoring and simulation. The core idea behind Digital Twin is to create an exact replica of a physical object in the virtual world, which can be used to monitor, simulate, and predict its behavior under varying operational conditions.

The Digital Twin model is built on three primary components: physical assets, virtual models, and data flow. The physical assets (e.g., CNC machine tools) are equipped with sensors to collect real-time data on parameters such as temperature, force, vibration, and position. This data is then transmitted to a virtual model, which serves as a digital replica of the physical system. The virtual model simulates the behavior of the physical system using sophisticated algorithms and machine learning techniques, enabling real-time predictions and optimizations.

One of the key advantages of Digital Twin technology is its ability to provide predictive insights. By continuously comparing the virtual model's predictions with actual system behavior, the Digital Twin can identify potential issues and predict future performance. In the context of tool wear, this means that a Digital Twin model can predict when a

tool is likely to fail based on real-time operational data, enabling predictive maintenance and minimizing downtime^[3].

2.4 Applications of Digital Twin in Manufacturing

Digital Twin technology has found wide applications in various sectors of manufacturing, ranging from process optimization to predictive maintenance. In CNC machining, Digital Twin models can be used to monitor and optimize machine performance in real-time, ensuring that the machine operates at its peak efficiency. For tool wear prediction, Digital Twin technology enables the creation of a virtual replica of the tool, where wear is tracked and predicted based on operational parameters such as cutting forces, temperature, and material interactions.

Furthermore, Digital Twin can be employed for condition-based maintenance by predicting tool life and suggesting optimal times for tool replacement or reconditioning. This minimizes unnecessary tool changes and avoids the consequences of tool failure. Additionally, by integrating Digital Twin with other advanced technologies such as AI and machine learning, manufacturers can develop intelligent systems that continuously learn and adapt to optimize the machining process.

In other manufacturing domains, Digital Twin is used for simulating complex systems, optimizing workflows, and monitoring production lines. It allows manufacturers to visualize the entire production process in a virtual space, thereby providing deeper insights into system performance and enabling better decision-making. The ability to simulate different conditions in a risk-free environment further accelerates innovation and product development.

3 APPLICATION OF DIGITAL TWIN IN TOOL WEAR PREDICTION

3.1 Digital Twin Architecture and Components

The architecture of a Digital Twin system for tool wear prediction consists of several layers, each of which plays a specific role in ensuring accurate monitoring and prediction. The first layer involves the collection of real-time data from physical sensors embedded in the CNC machine and the cutting tool. These sensors typically measure parameters such as cutting forces, vibration, temperature, and tool geometry changes.

The second layer is the data integration and processing layer, which includes data fusion algorithms that combine data from various sources to create a comprehensive view of the system's behavior. This layer also includes data preprocessing steps, such as noise reduction and normalization, to ensure the quality of the data used for simulation and prediction.

The third layer is the virtual model, which uses simulation algorithms to create a real-time digital replica of the CNC machine and the tool. This model incorporates information about the machine's kinematics, the tool's wear characteristics, and the machining process. The virtual model uses this data to simulate tool wear and predict future wear trends under different operational scenarios.

Finally, the last layer is the decision-making and feedback layer, which interprets the predictions made by the virtual model and provides actionable insights. These insights can include alerts for imminent tool failure, recommendations for tool replacement, or adjustments to the machining parameters to optimize performance^[4].

3.2 Data Acquisition and Processing in CNC Machines

Accurate data acquisition is the cornerstone of any Digital Twin system. In the context of CNC machine tools, sensors are placed at key locations on the machine to capture critical operational data. Cutting force sensors measure the forces applied to the tool during machining, while temperature sensors monitor the heat generated in the cutting zone. Vibration sensors capture the dynamic behavior of the machine, and position sensors track the tool's movements and any changes in geometry.

The data collected from these sensors is typically noisy and requires extensive preprocessing before it can be used for simulation and prediction. Techniques such as signal filtering, time-series analysis, and data fusion are employed to ensure the quality and accuracy of the data. Additionally, machine learning algorithms can be used to identify

patterns and correlations in the data that may not be immediately apparent, providing deeper insights into the tool wear process.

3.3 Tool Wear Modeling and Simulation

Once the data is collected and processed, it is used to create a dynamic model of the tool's wear process. Tool wear modeling can be performed using various techniques, such as finite element analysis (FEA), machine learning, and data-driven modeling. FEA allows for the simulation of the physical stresses and thermal loads acting on the tool, while machine learning algorithms can be trained on historical data to predict wear patterns^[5].

The simulation models take into account various factors, including the cutting conditions (e.g., speed, feed rate, and depth of cut), material properties, and tool geometry. By combining these models with the real-time data provided by the Digital Twin, it is possible to create highly accurate simulations of tool wear under different conditions.

3.4 Integration of Digital Twin and Tool Wear Prediction

The integration of Digital Twin technology with tool wear prediction systems is a key advancement in the field of predictive maintenance. Through continuous monitoring and simulation, Digital Twin models can predict the tool's remaining useful life (RUL) and identify any anomalies in the wear process. These predictions are based on real-time data, allowing for timely intervention before the tool experiences catastrophic failure.

By integrating the Digital Twin with decision-making algorithms, manufacturers can optimize tool life, reduce downtime, and minimize maintenance costs. The system can also recommend adjustments to machining parameters, such as cutting speed or feed rate, to reduce wear and improve overall efficiency.

In summary, the integration of Digital Twin technology in tool wear prediction provides a comprehensive and dynamic solution for improving the efficiency and reliability of CNC machining operations. By simulating and predicting tool wear in real-time, manufacturers can take proactive measures to extend tool life, enhance product quality, and optimize machining processes.

4 TOOL WEAR PREDICTION MODELS AND METHODS

4.1 Physics-Based Tool Wear Prediction Methods

Physics-based tool wear prediction methods are grounded in the fundamental principles of material science, thermodynamics, and mechanics. These models typically describe the wear process through the interactions between the tool and the workpiece, considering factors such as cutting forces, temperature distributions, and material properties. One of the most widely used physics-based models is the wear model based on cutting force and temperature, which suggests that the wear rate increases with higher cutting forces and temperature in the cutting zone.

The main advantage of physics-based models is their ability to predict wear under a wide range of machining conditions, as they are rooted in well-understood physical principles. These models often employ analytical equations, such as Archard's wear law or the predictive models based on friction and heat generation during the cutting process. However, they have limitations, particularly when it comes to capturing the complexity of real-world machining conditions. For example, factors such as tool material properties, workpiece material heterogeneity, and the dynamics of the cutting process can introduce significant variabilities that are difficult to account for in traditional physics-based models^[6].

Despite these challenges, physics-based models remain a cornerstone of tool wear prediction, especially when used in combination with empirical data or more advanced techniques like finite element analysis (FEA) to improve their accuracy.

4.2 Data-Driven Tool Wear Prediction Methods

Data-driven tool wear prediction methods leverage large amounts of historical data to identify patterns and

correlations between machining parameters and tool wear progression. These methods are typically based on statistical techniques and machine learning algorithms that learn from past tool wear events to make predictions about future tool behavior. The key advantage of data-driven methods lies in their ability to process vast amounts of real-time sensor data and adapt to new machining scenarios.

The most common data-driven approaches for tool wear prediction include regression analysis, time-series forecasting, and clustering techniques. Regression models, such as linear or nonlinear regression, attempt to correlate specific machining parameters (e.g., cutting speed, feed rate, material properties) with the observed wear rate. Time-series forecasting methods, including autoregressive integrated moving average (ARIMA) models and Long Short-Term Memory (LSTM) networks, analyze historical data over time to predict future wear trends. Clustering algorithms, such as k-means clustering, group similar tool wear patterns together, facilitating the identification of key indicators for wear progression.

While data-driven methods have demonstrated great potential, their accuracy depends heavily on the quality and quantity of data available. Additionally, these methods require continuous monitoring and real-time data collection to make accurate predictions, which can be resource-intensive.

4.3 Hybrid Models for Tool Wear Prediction

Hybrid models for tool wear prediction combine the strengths of both physics-based and data-driven approaches to create more robust and accurate predictions. These models are designed to overcome the individual limitations of each approach by blending the physical insights from traditional models with the adaptability of data-driven techniques. For example, a hybrid model might use physics-based equations to estimate the initial wear rate and then refine those predictions using machine learning algorithms that can adjust for real-time sensor data.

A typical hybrid approach may involve a two-step process: first, a physics-based model generates initial wear predictions based on predefined cutting conditions and material properties. Next, machine learning algorithms or statistical methods are applied to adjust these predictions using real-time data collected from sensors on the CNC machine. The advantage of this hybrid approach lies in its ability to integrate domain knowledge (from physics) with empirical observations (from data), offering more accurate and reliable predictions under a broader set of conditions^[7].

Hybrid models are increasingly popular in the field of predictive maintenance, as they offer a balance between theoretical accuracy and practical adaptability. However, the integration of different modeling techniques requires careful consideration of how data is processed and how the models are calibrated, as inconsistencies between the two approaches can reduce the effectiveness of the hybrid model.

4.4 Machine Learning and Deep Learning for Tool Wear Prediction

Machine learning (ML) and deep learning (DL) methods represent a significant leap forward in tool wear prediction, particularly due to their ability to process large volumes of complex data and detect intricate patterns that are difficult to model with traditional approaches. These methods rely on algorithms that learn from data and continuously improve as they are exposed to more information. The main advantage of ML and DL techniques is their ability to automatically extract features from raw sensor data, such as cutting forces, temperature, and vibrations, without the need for manual intervention.

Supervised learning methods, such as support vector machines (SVM), random forests, and neural networks, have been widely used in tool wear prediction. These models learn a mapping between input features (machining conditions, sensor data) and output (tool wear rate or tool life). A significant challenge in supervised learning is the need for a large and representative dataset of labeled training data, which can be difficult to obtain in real-world settings.

Deep learning, particularly convolutional neural networks (CNNs) and recurrent neural networks (RNNs), offers advanced capabilities for handling sequential and unstructured data. RNNs, such as Long Short-Term Memory (LSTM) networks, are especially useful for time-series data, where the relationship between past and future wear

patterns is critical. These models are capable of learning temporal dependencies in the wear process and can provide high-accuracy predictions even in the face of complex, nonlinear relationships between machining parameters and tool wear.

The growing use of deep learning in tool wear prediction is promising, as these models have demonstrated the potential to improve prediction accuracy significantly. However, they require large amounts of data for training, and their black-box nature can sometimes make it difficult to interpret the reasoning behind their predictions. Additionally, the deployment of deep learning models in industrial settings often involves significant computational overhead and requires real-time data processing capabilities. Despite these challenges, machine learning and deep learning remain at the forefront of tool wear prediction, offering powerful tools for improving the accuracy, adaptability, and efficiency of predictive maintenance strategies in CNC machining^[8].

5 CONCLUSION

In conclusion, the integration of Digital Twin technology into tool wear prediction represents a significant advancement in the field of CNC machining. By enabling real-time monitoring of tool condition and simulating wear processes through virtual models, Digital Twin provides an efficient and accurate platform for tool wear prediction and proactive maintenance. This paper reviewed various prediction models, including physics-based, data-driven, and hybrid approaches, highlighting the advantages and limitations of each method in the context of tool wear in CNC machines. Furthermore, the paper explored how Digital Twin can enhance the performance of these models by incorporating real-time data and simulation capabilities.

Despite the promising results, several challenges remain, including the need for high-quality, real-time data and the complexity of integrating advanced machine learning techniques with existing CNC systems. Future research should focus on optimizing the hybridization of data-driven and physics-based models, incorporating deep learning for improved predictive accuracy, and reducing the computational overhead of Digital Twin systems to enable real-time application in industrial settings.

Ultimately, the continuous evolution of Digital Twin technology and its integration with advanced predictive models will significantly improve the efficiency, reliability, and cost-effectiveness of CNC machining operations. The predictive maintenance strategies enabled by Digital Twin-based tool wear prediction will not only reduce machine downtime but also extend tool life, enhance the overall machining process, and contribute to the sustainability of manufacturing systems.

REFERENCES

- [1] Sun J, Wang D, Liu Z, et al. Tool digital twin based on knowledge embedding for precision CNC machine tools: Wear prediction for collaborative multi-tool[J].*Journal of Manufacturing Systems*,2025,80:157-175.
- [2] Xin Y, Yan R, Genbao Z, et al. A digital twin-driven hybrid approach for the prediction of performance degradation in transmission unit of CNC machine tool[J].*Robotics and Computer-Integrated Manufacturing*,2022,73
- [3] Xu Z, Selvaraj V, Min S. Intelligent G-code-based power prediction of ultra-precision CNC machine tools through 1DCNN-LSTM-Attention model[J].*Journal of Intelligent Manufacturing*,2024,36(2):1-24.
- [4] Tao W, Dailin Z. Improved Prediction Model of the Friction Error of CNC Machine Tools Based on the Long Short Term Memory Method[J].*Machines*,2023,11(2):243-243.
- [5] Wang X, Wu H, Yang J, et al. Modeling and prediction method for inherent energy consumption of CNC machine tool spindle systems[J].*Journal of Mechanical Science and Technology*,2025,39(7):1-17.
- [6] Sun J, Wang D, Liu Z, et al. Tool digital twin based on knowledge embedding for precision CNC machine tools: Wear prediction for collaborative multi-tool[J].*Journal of Manufacturing Systems*,2025,80:157-175.
- [7] Guoyong Z, Chunxiao L, Zhe L, et al. Specific energy consumption prediction model of CNC machine tools based on tool wear[J].*International Journal of Computer Integrated Manufacturing*,2020,33(2):159-168.
- [8] AMJATH A Z, MOORTHY G R, ALI A S K, et al. MACHINE LEARNING-BASED PREDICTION OF SURFACE CHARACTERISTICS AND TOOL WEAR IN Mg–AZ91D MILLING UNDER DISTINCT CONDITIONS[J].*Surface Review and Letters*,2025(prepublish).